

VOIPLI SPECS

Model Features	SOHO	SMB FXS/FXO	SMB E1 30 TDM CH.	Corporate	Enterprise
FXO/FXS Ports	Up to 4	Up to 16	Up to 16	Up to 500 Ports	Up to 4000 Ports
PRI	-	-	1	Up to 4	Up to 4
SIP Channels (Voipli lines)	5	15	15	90	120
Extensions. (remote , local & Mobile)	10	50		500	5000
Full Interconnection With Coral/Panasonic	-	-	Digital Trough E1		
Intercom/ Pan Code	Yes				
PBX Interconnectivity	Yes				
Sip Trunk Capacity (against bandwidth)	5 Channels	15 CH/1Mb/sec	30 CH/1Mb/sec	120CH/2Mb/sec	
Conference Rooms/Participants	NO	1 room/ 10 participants	5/30	unlimited	
Codecs	G729/G711/GSM				
Hard Disk (SATA)	SSD 16 GB	160 Gb 2.5"	320 GB X 2	500 GB X 2	
Redundancy/ RAID	No			Yes	
CPU	Intel ATOM N270 1.6 Ghz Single Core	Intel ATOM DM510 Dual Core 1.8 GHz	i3 2.8 GHz	Xeon Dual/ Quad Core 3+ GHz	
RAM Existing/Expandable	1Gb/ DDR2 800 Mhz	2Gb/ DDR2 800 Mhz	2Gb/ DDR3 1300 Mhz	4Gb/ DDR3	
Power Supply/redundancy	12 VDC / 3.5A		230 VAC 350W	2 X 500W/yes	
Operation System	Voipli 2.1 Linux/ Asterisk based				
User Friendly Interface	Voipli Operation Panel (VOP) Ver 2.0				
Position	Hor/ Vert	Rack Mount. 1 U			
Weight	1.5 Kg	3.5 Kg	5.5 Kg	18 Kg.	

Due to constant improvement specs may change without previous advice. All rights reserved